

Black Steel Blind ANSI 150

<u>SIZE</u> (mm)	<u>CODE</u>	<u>WORKING PRESSURE</u> kPa (Atmospheric)	<u>MATERIAL</u>
25	SA150025B	17,700	Carbon Steel
32	SA150032B	17,700	Carbon Steel
40	SA150040B	17,700	Carbon Steel
50	SA150050B	17,700	Carbon Steel
65	SA150065B	17,700	Carbon Steel
80	SA150080B	17,700	Carbon Steel
100	SA150100B	17,700	Carbon Steel
125	SA150125B	17,700	Carbon Steel
150	SA150150B	17,700	Carbon Steel
200	SA150200B	17,700	Carbon Steel

*In accordance with AS2129

Flange Dimensions

<u>SIZE</u> (mm)	<u>Number of Holes</u>	<u>Flange Diameter</u>	<u>Pitch Circle Diameter</u>	<u>Bolt Hole Diameter</u>	<u>Flange Thickness</u>
		(mm) A	(mm) B	(mm) C	(mm) D
25	4	108	79.2	15.7	14.2
32	4	117.3	88.9	15.7	15.7
40	4	127	98.6	15.7	17.5
50	4	152.4	120.7	19.1	19.1
65	4	177.8	139.7	19.1	22.4
80	4	190.5	152.4	19.1	23.9
100	8	228.6	190.5	19.1	23.9
125	8	254	215.9	22.4	23.9
150	8	279.4	241.3	22.4	25.4
200	8	342.9	298.5	22.4	28.4

- CTS Copper Capillary Socket Fittings manufactured in accordance with AS 3688
- Adapters meet requirements of a maximum operating pressure of 1.4MPa where working temperature
- Electrolysis Insulator made from EDPM rubber to prevent contact from Steel Backing Flange and Copper

