

Black Steel Slip On Flange **Table D**

<u>Size (mm)</u>	<u>Code</u>	<u>Working Pressure kPa (Atmospheric)</u>	<u>Max Hydrostatic Test Pressure, kPa*</u>	<u>Material</u>
100	STD100	700	1,050	Carbon Steel
125	STD125	700	1,050	Carbon Steel
150	STD150	700	1,050	Carbon Steel
200	STD200	700	1,050	Carbon Steel

*In accordance with AS2129

Flange Dimensions

<u>SIZE (mm)</u>	<u>Number of Holes</u>	<u>Flange Diameter (mm)</u> A	<u>Pitch Circle Diameter (mm)</u> B	<u>Bolt Hole Diameter (mm)</u> C	<u>Flange Thickness (mm)</u> D	<u>Bore Hole (mm)</u> F
100	4	215	178	18	12	114.7
125	8	255	210	18	12	141.7
150	8	280	235	18	13	168.7
200	8	335	292	18	15	219.5

- CTS Copper Capillary Socket Fittings manufactured in accordance with AS 3688
- Adapters meet requirements of a maximum operating pressure of 1.4MPa where working temperature
- Electrolysis Insulator made from EDPM rubber to prevent contact from Steel Backing Flange and Copper

